

 HDA

GUIDE

HDMI Cables (4K & 8K)

CONNECT

48G ULTRA HIGH SPEED SLIMWIRE MAX

4K Premium High Speed

SLIMWIRE MAX HDMI CABLE



No other HDMI cable will give you better picture and sound from your 4K TV setup. Supporting the full HDMI 2.0 (a/b) 18Gbps max data rate end-to-end.

Capable of carrying the most premium UHD/4K 60 4:4:4 content, along with all HDR formats (10 & 12-bit), Dolby Vision, HDR10+ and HLG.

Features

HDMI® 2.0 compliant (a/b)
HDCP 2.2 compliant
18Gbps data rate
Supports all resolutions up to and inc. 4K Ultra HD 60fps 4:4:4
Supports all current High Dynamic Range (HDR) formats
Supports all current audio formats 5.1/7.1 Lossless Dolby TrueHD and DTS+HD Surround Sound, Dolby Atmos and DTS:X
Supports CEC, HDMI Ethernet channel, and ARC features
Precision manufactured
Low capacitance dielectric
3-layer shielding provides superior rejection of EM and RF interference
24K Gold Plated HDMI male connectors
RoHS Certified



Specification

Available Sizes	0.25, 0.5, 0.8, 1, 1.5, 2, 3, 4, & 5 metres.
Thickness	30 AWG (5m 28 AWG) 99.9% high purity oxygen-free copper conductor
Colour	Black
Conductors	99.99% oxygen free copper
Insulation (inner jacket)	High-density polyethylene (HD-PE)
Layers 1 & 2 Shielding	100% Aluminium Foil
Layer 3 Shielding	95% Al+My braid
Insulation (outer jacket)	PVC
Contacts	Gold plated
Configuration	19+1 Pin
Guarantee	5-year guarantee

LENGTHS & SKUS

0.25m	1.55.901.037.1	2.0m	1.55.901.004.1
0.5m	1.55.901.001.1	3.0m	1.55.901.005.1
0.8m	1.55.901.036.1	4.0m	1.55.901.006.1
1.0m	1.55.901.002.1	5.0m	1.55.901.007.1
1.5m	1.55.901.003.1		

ACTIVEWIRE MAX HDMI CABLE



ActiveWire Max is a long-range active HDMI cable with maximum bandwidth capabilities. Supporting the full HDMI 2.0 (a/b) 18Gbps max data rate end-to-end. Capable of carrying the most premium UHD/4K 60 4:4:4 content, along with all HDR formats (10 & 12-bit), Dolby Vision, HDR10+ and HLG.

The source-end of an ActiveWire Max HDMI cable incorporates an advanced TMDs equalisation chipset, that effectively filters electrical noise and interference from the HDMI transmission. This outcome is an increased transmission distance that enables ActiveWire long-range cables to pass the same data rates as much shorter cables.

Features

HDMI® 2.0 compliant (a/b)
HDCP 2.2 compliant
18Gbps High Speed data rate (end-to-end)
Supports all resolutions up to and inc. Ultra HD 4K 60fps 4:4:4
Supports all current High Dynamic Range (HDR) formats
Supports all current audio formats 5.1/7.1 Lossless Dolby TrueHD and DTS-HD Sur round Sound, Dolby Atmos and DTS:X
Supports CEC, HDMI Ethernet channel, and ARC features
Active copper (directional) cable with optional source-end USB-power for use as re quired
Precision manufactured
26 AWG 99.9% high purity oxygen-free copper conductor (8m and 10m)
24 AWG 99.9% high purity oxygen-free copper conductor (15m and 20m)
Low capacitance dielectric
3-layer shielding provides superior rejection of EM and RF interference
24K Gold Plated HDMI male connectors
RoHS Certified

Specification

Available Sizes	10 &15 metres.
Thickness	26 gauge (10m) / 24 gauge (15m)
Colour	Black
Conductors	99.99% oxygen free copper
Insulation (inner jacket)	High-density polyethylene (HD-PE)
Layers 1 & 2 Shielding	100% Aluminium Foil
Layer 3 Shielding	95% Al+My braid
Insulation (outer jacket)	PVC
Contacts	Gold plated
Configuration	19+1 Pin
Voltage	5v (USB)
Guarantee	5-year guarantee

LENGTHS & SKUS

10.0 m1.55.901.016.3

15.0 m1.55.901.017.3



8K Ultra High Speed

SLIMWIRE MAX (48G) HDMI CABLE



No other HDMI cable will give you better picture and sound from your 8K TV setup. Supporting the full HDMI 2.1 (a/b) 48Gbps max data rate end-to-end.

Capable of carrying the most premium ultra high speed 8K 60 4:4:4 content, along with all HDR formats (10 & 12-bit), Dolby Vision, HDR10+ and HLG.

Features

HDMI® 2.1 compliant (a/b)
HDCP 2.3 compliant
Uncompressed 8K@60fps 4:4:4, 4K@120fps and 10K@30fps
Officially Certified for 48G
Static/dynamic HDR, HDR10 & Dolby Vision
21:9 screen ratio support
Enhanced Audio Return Channel (eARC)
Ethernet Channel & CEC supported
DTS Master, DTS:X, Dolby TrueHD, & Dolby Atmos Audio
Supports: VRR, ALLM, QMS, QFT
Small precision-manufactured compact aluminium headshell assembly
24K Gold Plated HDMI male connectors

Specification

Available Sizes	0.5, 1, 1.5, 2, 3, 4, metres
Thickness	30 AWG (5m 28 AWG) 99.9% high purity oxygen-free copper conductor
Colour	Carbonite
Conductors	OFHC (Oxygen-Free High-Conductivity) copper
Insulation (inner jacket)	High-density polyethylene (HD-PE)
Layers 1 & 2 Shielding	100% Aluminium Foil
Layer 3 Shielding	95% Al+My braid
Insulation (outer jacket)	PVC
Contacts	Gold plated
Configuration	19+1 Pin
Guarantee	5-year guarantee

LENGTHS & SKUS

0.5m	1.55.917.001.1	3.0m	1.55.917.005.1
1.0m	1.55.917.002.1	4.0m	1.55.917.006.1
1.5m	1.55.917.003.1		
2.0m	1.55.917.004.1		



8K Ultra High Speed

FIBRE-OPTIC MAX (48G) HDMI CABLE



No other HDMI cable will give you better picture and sound from your 8K TV setup. Supporting the full HDMI 2.1 (a/b) 48Gbps max data rate end-to-end.

Capable of carrying the most premium ultra high speed 8K 60 4:4:4 content, along with all HDR formats (10 & 12-bit), Dolby Vision, HDR10+ and HLG.

Features

HDMI® 2.1 compliant (a/b)
HDCP 2.3 compliant
Uncompressed 8K@60fps 4:4:4, 4K@120fps and 10K@30fps
Officially Certified for 48G
Static/dynamic HDR, HDR10 & Dolby Vision
21:9 screen ratio support
Enhanced Audio Return Channel (eARC)
Ethernet Channel & CEC supported
DTS Master, DTS:X, Dolby TrueHD, & Dolby Atmos Audio
Supports: VRR, ALLM, QMS, QFT
Small precision-manufactured compact aluminium headshell assembly
24K Gold Plated HDMI male connectors

Specification

Available Sizes	15 & 20 metres
Thickness	17.3mm/0.6in
Colour	Carbonite
Max. Bend Radius	6cm/2.36in
Max. Pull Tension	15kg/33lbs
Operating temperature	14°F ~ 122°F (-10°C ~ 50°C) 10% ~ 90%, non-condens
Storage temperature	-4°F ~ 140°F (-20°C ~ +60°C) 10% ~ 90%, non-condens
Insulation (outer jacket)	PVC
Contacts	Gold plated
Configuration	19 Pin
Power Supply	Passive HDMI: 5V 4.5v~5.5v VCC
Guarantee	5-year guarantee

LENGTHS & SKUS

15.0m 1.55.918.003.1 **20.0m** 1.55.918.004.1



≡ ≡ HDA